

Appl. No. **09/934,549**  
Amdt. dated 01/30/2008  
Response to Office Action of 12/31/2007

Attorney Docket No.: TS01-285  
N1085-90132

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) A component transport cart, comprising:
  - (a) a lower portion, said lower portion comprising:
    - (i) wheels providing capabilities of motion to said transport cart;
    - (ii) a platform having a first and a second surface opposite said first surface, said wheels being attached to said first surface of said platform;
    - (iii) shock absorbers, being mounted on the second surface of said platform;
  - (b) an upper portion disposed over said shock absorbers, said shock absorbers forming an interface between said platform and said upper portion, said upper portion comprising:
    - (i) a front surface being located in a plane;
    - (ii) a back surface being parallel with said front surface;
    - (iii) a planar bottom surface being orthogonal to said front and back surfaces;
    - (iv) a top surface being parallel with said bottom surface;
    - (v) a left surface being located on in a plane orthogonal to said planar bottom surface;
    - (vi) a right surface being parallel with said left surface;

Appl. No. **09/934,549**  
Amdt. dated 01/30/2008  
Response to Office Action of 12/31/2007

Attorney Docket No.: TS01-285  
N1085-90132

17 (vii) upper portion dividers provided in a plane parallel with said left and right  
18 surfaces;

19 (viii) component box support units being mounted in a box support plane and  
20 capable of supporting a component box, adjacent rows of component box support units  
21 being separated by a distance, said component box support units:

22 (1) extending from said front surface of said component cart to said back surface  
23 of said component cart;

24 (2) being arranged along said upper portion dividers and said left and right  
25 surfaces;

26 (3) including cushioning units arranged over the surface of said component box  
27 support units;

28 (4) including said box support plane angled with respect to said planar bottom  
29 surface;

30 (ix) a set of two sliding doors mounted in a plane of said front surface of said  
31 component cart; and

32 (x) a handle attached to said upper portion, enabling motion of said component  
33 cart.

1 2. (Currently Amended) The component cart of claim 1, wherein said  
2 component box ~~comprising~~ comprises a reticle box[[.]] with a reticle ~~having been placed~~  
3 disposed inside said reticle box ~~prior to insertion of said reticle into said component~~  
4 ~~transport cart.~~

1 3. (Currently Amended) The component cart of claim 1, said component cart  
2 formed of ~~being created using~~ anti-Electro Static Discharge materials.

Appl. No. **09/934,549**  
Amdt. dated 01/30/2008  
Response to Office Action of 12/31/2007

Attorney Docket No.: TS01-285  
N1085-90132

1           4.       (Withdrawn) A method of transporting components, comprising the steps  
2 of:

3           loading said components into a component box;

4           providing a component cart, said component cart comprising a lower portion  
5 comprising wheels providing capabilities of motion to said transport cart, said lower  
6 portion further comprising a platform having a first and an opposed second surface, said  
7 wheels being attached to said first surface of said platform,

8           shock absorbers mounted on the second surface of said platform.

9           said component cart further comprising an upper portion comprising surfaces  
10 forming a cubic structure, said upper portion interfacing with said shock absorbers of  
11 said lower portion, said shock absorbers disposed between said platform and said  
12 upper portion,

13          said upper portion further comprising component box support units being  
14 mounted in a plane, said plane of said component box support units slanting in a  
15 downward direction with respect to a plane of said platform of said lower unit,  
16 cushioning units arranged over the surface of said component support units, adjacent  
17 rows of said component support units being separated by a distance, said upper portion  
18 of said component cart having a front surface, said front surface comprising sliding  
19 doors allowing access to said component cart;

20          sliding one of said front doors, providing access to said component cart;

21          positioning a component box inside the component cart;

22          sliding one of said front doors, inhibiting access to said component cart; and

23          moving said component cart to a location.

Appl. No. 09/934,549  
Amdt. dated 01/30/2008  
Response to Office Action of 12/31/2007

Attorney Docket No.: TS01-285  
N1085-90132

1           5.     (Withdrawn) The method of claim 4, said upper portion comprising:  
2           said front surface being located in a plane;  
3           a back surface being parallel with said front surface;  
4           a planar bottom surface being orthogonal to said front and back surfaces;  
5           a top surface being parallel with said bottom surface;  
6           a left surface being located on a plane that is orthogonal to said planar bottom  
7 surface;  
8           a right surface being parallel with said left surface; and  
9           a handle attached to said upper portion, enabling motion of said component cart.

1           6.     (Withdrawn) The method of claim 4, said component support units  
2 comprising:

3           (1) being extended from said front surface of said component cart to said back  
4 surface of said component cart;

5           (2) component supports spatially arranged along sidewalls of said component  
6 support units; and

7           (3) cushioning units arranged over the surface of said component support units.

1           7.     (Withdrawn) The method of claim 4, said component box comprising a  
2 reticle box, a reticle having been inserted in said reticle box prior to insertion of said  
3 reticle box into said component cart.

Appl. No. **09/934,549**  
Amtd. dated 01/30/2008  
Response to Office Action of 12/31/2007

Attorney Docket No.: TS01-285  
N1085-90132

8. (Withdrawn) The method of claim 4, said component cart being created using anti-Electro Static Discharge materials.

1 9. (New) The component cart of claim 1, wherein said sliding doors are  
2 formed of anti-Electro Static Discharge materials.

1 10. (New) The component cart of claim 1, wherein said box support plane is  
2 orthogonal with respect to said left and right surfaces and angled downwardly from said  
3 front surface.

1 11. (New) The component cart of claim 1, further comprising a plurality of  
2 reticle boxes, each with a reticle therein, said reticle boxes laterally disposed and each  
3 supported by a corresponding component box support unit.